
SPACER PROFILE

DESCRIPTION

U-shaped galvanised steel profile measuring 26 mm in width and length according to the gap between profiles. It is a U-shaped profile used to fix the distance between profiles that form the false ceiling structure during installation. It has slots for T-shaped profile heads (T15, T24, T35, T-Decor15, T-Decor24 and Murano profile), spaced apart by a distance equal to the distance to be set.



MATERIAL

Profiles formed by folding S250 GD + Z galvanised steel sheets with a thickness of 0.70±0.05 mm in accordance with the UNE-EN 10143 standard, with the supplier's quality certificate.

PROPERTIES

Reaction to Fire

Class A1 (No contribution to Fire, formerly M0), according to Royal Decree RD 842/2013 dated 23/11/2013 in Annex I, point 1.2, which establishes said classification for construction products manufactured in steel (not in finely divided form) without the need for testing.

SUPPLY

Perimeter profile	Units per pack	Weight per pack
0.60 m	20	4 kg
1.20 m	20	8 kg
0.30 m	20	2 kg

The pallets have a 14-pack base (1.20 m spacer) or 28-pack base (0.60 m spacer).

UPDATED VERSION

To view the latest version of this document, scan this QR code.

Version 0
14/02/2025

THU Ceiling Solutions reserves the right to change the content of this document without prior notice. Every effort has been made to ensure that the content of this publication is accurate, but THU Ceiling Solutions accepts no liability for any errors or potentially misleading information. Suggestions regarding the end use or application of the products or working methods are for information purposes only and THU Ceiling Solutions accepts no liability in this regard.

Masía de Monte Alcedo Parcela, 4.3
P.I. Masía Baló, 46394 Ribarroja del Turia, Valencia

Phone. 96 134 05 44
Fax. 96 166 78 21

info@thu.es
www.thu.es